

SPECIFICATIONS

Engine Type	
<i>Manual</i>	3.2-liter (3179 cc), DOHC, V-6
<i>Automatic</i>	3.0-liter (2977 cc), DOHC, V-6
Horsepower, SAE net	
<i>Manual</i>	290 hp @ 7100 rpm
<i>Automatic</i>	252 hp @ 6600 rpm
Torque, SAE net	
<i>Manual</i>	224 lbs-ft @ 5500 rpm
<i>Automatic</i>	210 lbs-ft @ 5300 rpm
Redline	
<i>Manual</i>	8000 rpm
<i>Automatic</i>	7500 rpm
Bore & Stroke	
<i>Manual</i>	3.66 in x 3.07 in (93.0 mm x 78.0 mm)
<i>Automatic</i>	3.54 in x 3.07 in (90.0 mm x 78.0 mm)
Displacement	
<i>Manual</i>	194 cu in (3179 cc)
<i>Automatic</i>	181 cu in (2977 cc)
Compression Ratio	10.2:1
Induction System	Programmed Fuel Injection (PGM-FI) with Variable Volume Induction System
Valvetrain	4 valves per cylinder, belt-driven, dual overhead camshafts with Variable Valve Timing and Lift Electronic Control (VTEC) system
Engine Block	
<i>Manual</i>	Aluminum alloy with FRM cylinder liners
<i>Automatic</i>	Aluminum alloy with cast-iron cylinder liners
Cylinder Head	Aluminum alloy
Connecting Rods	Titanium
Emission Control	3-way catalytic converter
Ignition System	Electronic direct ignition
Alternator	12V, 120 amp. max
Battery	12V, 65 amp/hr., maintenance-free
Front Suspension	Independent aluminum double- wishbone with coil springs, stabilizer bar and compliance pivot
Rear Suspension	Independent aluminum double- wishbone with coil springs and stabilizer bar

SPECIFICATIONS

Recommended Fuel	Premium unleaded 91 octane
Body Type	All-aluminum unit body
Shock Absorbers	Telescopic/gas-filled, front & rear
Steering Type	Electric, variable power-assist, rack-and-pinion
Steering Ratio	18.6:1
Steering Wheel Turns, lock-to-lock	3.07
Turning Circle, curb-to-curb	38.1 ft (11.6 m)
Wheels	Forged aluminum alloy
<i>Front</i>	16 x 7 JJ
<i>Rear</i>	17 x 8.5 JJ
Tires	
<i>Front</i>	215/45 ZR 16
<i>Rear</i>	245/40 ZR 17
Braking System	Dual-diagonal, power-assisted, 4-wheel ventilated disc brakes; 4-channel Anti-Lock Braking System (ABS)
<i>Front Discs</i>	Ventilated, 11.7 in (298 mm) diameter, 28 mm rotor thickness
<i>Rear Discs</i>	Ventilated 11.9 in (303 mm) diameter, 23 mm rotor thickness
<i>Swept Area</i>	
<i>Front</i>	221.1 in (1426 cm ²)
<i>Rear</i>	229.2 in (1479 cm ²)
<i>Parking Brake</i>	Rear, mechanical

POWERTRAIN

Type	Transverse midship-engine/rear- wheel drive	
Transmission	6-speed manual	4-speed electronically controlled automatic with programmed lockup torque converter and SportShift (optional)
Ratios (:1)		
1st	3.066	2.611
2nd	1.956	1.551
3rd	1.428	1.025
4th	1.125	0.684
5th	0.914	—
6th	0.717	—
Reverse	3.186	1.909
Final Drive	4.062	4.428

CAPACITIES

Crankcase	<i>Including filter</i> 6.7 U.S. quarts (6.3 liters)
Cooling System	
<i>Manual</i>	16.9 U.S. quarts (16.0 liters)
<i>Automatic</i>	17.4 U.S. quarts (16.5 liters)
Fuel Tank	18.5 U.S. gallons (70 liters)
Passenger Volume	48.9 cu ft
EPA Cargo Volume	5.0 cu ft
Total Volume	53.9 cu ft

FUEL ECONOMY

Factory Estimated Fuel Mileage, City/Highway*

17/24 (manual) 18/24 (automatic)

**Use for comparison purposes only. California figures are the same.
Your mileage may vary.*

EXTERIOR DIMENSIONS

Wheelbase	99.6 in (2530 mm)
Track, front	59.4 in (1510 mm)
Track, rear	60.2 in (1530 mm)
Length	174.2 in (4425 mm)
Overall width	71.3 in (1810 mm)
Height	46.1 in (1170 mm)
Curb Weight	<i>Coupe</i> <i>NSX-T</i>
<i>Manual</i>	3069 lbs (1392 kg) 3164 lbs (1435 kg)
<i>Automatic</i>	3113 lbs (1412 kg) 3208 lbs (1455 kg)
Weight Distribution (%F/R)	42 / 58
Coefficient of Drag (Cd)	0.32
Coefficient of Lift (Cl)	0.05
Frontal Area (A)	19.16 sq ft (1.78 m ²)
Air Drag Coefficient (CD x A)	0.57

INTERIOR DIMENSIONS

Head Room	36.3 in (921 mm)
Leg Room	44.3 in (1126 mm)
Hip Room	53.8 in (1366 mm)
Shoulder Room	52.5 in (1334 mm)

WARRANTIES

Vehicle	4-year/50,000-mile limited warranty
Outer Body Rust-Through	5-year/unlimited-mile limited warranty
Roadside Assistance (TLC)	4-year/50,000-miles