

POWERTRAIN																						
Engine Type	Turbocharged 2.3-liter, 16-valve, DOHC i-VTEC [®] inline 4-cylinder																					
Horsepower, SAE net	240 hp at 6000 rpm																					
Torque, SAE net	260 lb-ft at 4500 rpm																					
Redline	6800 rpm																					
Bore and Stroke	3.4 x 3.9 inches (86 x 99 mm)																					
Displacement	2300 cc																					
Compression Ratio	8.8:1																					
Maximum turbocharger boost	13.5 psi																					
Induction System	Multi-Point Fuel Injection																					
Valvetrain	intelligent Variable Valve Timing and Lift Electronic Control (i-VTEC [®]), 4 valves per cylinder, DOHC																					
Engine Block	Die-cast lightweight aluminum alloy																					
Emission Certification	EPA TIER 2 – BIN 5 and CARB LEV II ULEV																					
Throttle	Drive-By-Wire [™] throttle system																					
Ignition System	Direct ignition system with knock control																					
Alternator	12V-105AH																					
Battery	12V-65AH																					
Recommended Fuel	Premium Unleaded																					
Layout	Transversely mounted, front-engine																					
Drivetrain	Super Handling All-Wheel Drive [™] (SH-AWD [™])																					
Transmission	Sequential SportShift 5-speed automatic with F1 [®] -style paddle shifters and Grade Logic Control																					
	<table><tr><td>Ratios (:1)</td><td>1st</td><td>2.697</td></tr><tr><td></td><td>2nd</td><td>1.606</td></tr><tr><td></td><td>3rd</td><td>1.071</td></tr><tr><td></td><td>4th</td><td>0.766</td></tr><tr><td></td><td>5th</td><td>0.612</td></tr><tr><td></td><td>Reverse</td><td>1.889</td></tr><tr><td></td><td>Final</td><td>4.533</td></tr></table>	Ratios (:1)	1 st	2.697		2 nd	1.606		3 rd	1.071		4 th	0.766		5 th	0.612		Reverse	1.889		Final	4.533
Ratios (:1)	1 st	2.697																				
	2 nd	1.606																				
	3 rd	1.071																				
	4 th	0.766																				
	5 th	0.612																				
	Reverse	1.889																				
	Final	4.533																				

CHASSIS

Body Type	All-steel unit body
Front Suspension	MacPherson strut independent
Rear Suspension	Independent multi-link
Shock Absorbers	Front and rear twin tube
Stabilizer Bars	21 mm diameter (front); 19 mm diameter (rear)
Steering Type	Torque-sensing variable power-assisted, rack-and-pinion
Steering Ratio	15.1:1
Steering Wheel Turns (lock-to-lock)	2.76
Turning Circle (curb-to-curb)	39.2 feet
Wheels	18x5-inch cast aluminum alloy wheels
Tires	P235/55R18 99V high performance all-season
Braking System	4-wheel Anti-lock Braking System (ABS) with Electronic Brake Distribution (EBD) and Brake Assist
Front Brakes	11.7-inch (296 mm) diameter ventilated disc with dual-piston calipers
Rear Brakes	12.0-inch (305 mm) diameter solid disc with single-piston calipers
Stability Control	Vehicle Stability Assist [™] (VSA [®]) with Traction Control System

CAPACITIES

Cooling System (total)	2.4 gallons/9.1 liters
Fuel tank	18 gallons/68.0 liters
Volumes	Passenger - 101.4 cubic feet Cargo with rear seats up - 27.8 cubic feet Cargo with rear seats down - 60.6 cubic feet
Engine Oil	Change with oil filter - 4.97 quarts/4.7 liters Total - 6.13 quarts/5.8 liters

FUEL ECONOMY

EPA Fuel Mileage (city/highway)

17/22 mpg*

*Based on 2008 EPA mileage estimates, reflecting new EPA fuel economy methods beginning with 2008 models. Use for comparison purposes only. Do not compare to models before 2008. Your actual mileage will vary depending on how you drive and maintain your vehicle.

EXTERIOR DIMENSIONS

Wheelbase	104.3 in	(2650 mm)
Track, front	61.9 in	(1572 mm)
Track, rear	62.6 in	(1590 mm)
Overall Length	180.7 in	(4590 mm)
Overall Width	73.6 in	(1869.4 mm)
Overall Height	65.2 in	(1656.1 mm)
Minimum Ground Clearance (full load)	5.12 in	(130 mm)
Approach/Departure Angle	Approach – 28.0 degrees Departure – 22.0 degrees Breakover – 18.5 degrees	

WEIGHTS

Curb Weight	3933 lbs (1784 kg)	with Technology Package - 3942 lbs (1788 kg)
Weight Distribution (% front / rear)	57/43	

TOWING

Maximum Towing Capacity	1500 lbs
-------------------------	----------

INTERIOR DIMENSIONS

Front	Head Room	38.7 in	(982 mm)
	Leg Room	41.8 in	(1062 mm)
	Hip Room	54.4 in	(1383 mm)
	Shoulder Room	58.2 in	(1479 mm)
2 nd Row	Head Room	38.3 in	(972 mm)
	Leg Room	37.7 in	(954 mm)
	Hip Room	53.0 in	(1347 mm)
	Shoulder Room	56.3 in	(1430 mm)

WARRANTY

Vehicle	4-year/ 50,000-mile limited warranty
---------	--------------------------------------

Powertrain	6-year / 70,000-mile limited warranty
------------	---------------------------------------

Outer Body Rust-Through	5-year / unlimited-mile limited warranty
-------------------------	--